


LED surface-mounted luminaire



Product-Nr.	111913-01
EAN:	4260556620954
Model:	TOPLED
Order number:	111913-01
Model:	TOPLED
Type:	LED surface-mounted luminaire
Illuminant:	High Power LED
Power consumption:	~8,4 W
Lamp luminous flux:	982 lm
Lamp luminous efficiency:	116 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Connection (connector):	M12 A-coded with connection cable
Degree of protection:	IP67
Class of protection:	III
Glare control:	ESG matt, shatterproof
Beam angle (optics):	40°
Operating temperature:	-10 °C -> +60 °C (14 °F -> 140 °F)
Colour rendering (Ra):	>80
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	4 mm safety glass
Height [B] x Width [C]:	Ø 50 mm (~1,97"), 23 mm (~0,91") built-up
Weight (net):	100 g (~4 oz)
Gross weight:	300 g (~11 oz)
Risk group (DIN EN 62471):	group 1
Markings:	CE, UKCA
Dimmable:	optional via accessories
Mounting accessories:	Nut M18x1.5 incl.
Made in:	Germany
Feature:	very bright