

## LED surface mounted tube luminaire



<b>Product-Nr.</b>	115210-02
<b>EAN:</b>	4260556621739
<b>Model:</b>	INROLED_70 mit Borosilikatglas-Schutzrohr

Order number:	115210-02
Model:	INROLED_70 mit Borosilikatglas-Schutzrohr

Type:	LED surface mounted tube luminaire
Illuminant:	SMD LED

Total output incl. driver:	~15 W
Power consumption:	~13 W

Lamp luminous flux:	2004 lm
Lamp luminous efficiency:	~155 lm/W

Light distribution:	direct
Light colour:	5600K 3-step MacAdam

Connected load:	90-305V AC $\pm$ 10%, 50-60 Hz
Power supply:	inbuilt

Connection (connector):	Cable entry, internal clamp
Degree of protection:	IP67/IP69K

Class of protection:	I
Glare control:	Microprisms

Beam angle (optics):	125°
Operating temperature:	-10 °C -> +40 °C (14 °F -> 104 °F)

Colour rendering (Ra):	>85
Lamps lifetime:	> 100.000h (L80/B10)

Housing material:	aluminium inside
Cover material:	safety glass, shatterproof

Height [B] x Width [C]:	Ø 70 mm (~2,76")
Length [A]:	650 mm (~25,59")

Weight (net):	2400 g (~85 oz)
Gross weight:	3050 g (~108 oz)

Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA

Mounting accessories:	optional
Made in:	Germany

Feature:	cascadable
cascadable:	yes

