

LED surface mounted tube luminaire



|                    |   |
|--------------------|---|
| <b>Product-Nr.</b> | 115110-02                                 |
| <b>EAN:</b>        | 4260556621722                             |
| <b>Model:</b>      | INROLED_70 mit Borosilikatglas-Schutzrohr |

|                            |   |
|----------------------------|---|
| Order number:              | 115110-02                                 |
| Model:                     | INROLED_70 mit Borosilikatglas-Schutzrohr |
| Type:                      | LED surface mounted tube luminaire        |
| Illuminant:                | SMD LED                                   |
| Total output incl. driver: | ~14 W                                     |
| Power consumption:         | ~11 W                                     |
| Lamp luminous flux:        | 1670 lm                                   |
| Lamp luminous efficiency:  | ~155 lm/W                                 |
| Light distribution:        | direct                                    |
| Light colour:              | 5600K 3-step MacAdam                      |
| Connected load:            | 90-305V AC ± 10%, 50-60 Hz                |
| Power supply:              | inbuilt                                   |
| Connection (connector):    | Cable entry, internal clamp               |
| Degree of protection:      | IP67/IP69K                                |
| Class of protection:       | I   |
| Glare control:             | Microprisms                               |
| Beam angle (optics):       | 125°                                      |
| Operating temperature:     | -10 °C -> +40 °C (14 °F -> 104 °F)        |
| Colour rendering (Ra):     | >85                                       |
| Lamps lifetime:            | > 100.000h (L80/B10)                      |
| Housing material:          | aluminium inside                          |
| Cover material:            | safety glass, shatterproof                |
| Height [B] x Width [C]:    | Ø 70 mm (~2,76")                          |
| Length [A]:                | 513 mm (~20,2")                           |
| Weight (net):              | 1950 g (~69 oz)                           |
| Gross weight:              | 2600 g (~92 oz)                           |
| Risk group (DIN EN 62471): | free group                                |
| Markings:                  | CE, UKCA                                  |
| Mounting accessories:      | optional                                  |
| Made in:                   | Germany                                   |
| Feature:                   | cascadable                                |
| cascadable:                | yes                                       |

