

IC6CLASS-TR

CEILING LOUDSPEAKERS In-ceiling / In-wall High-End Loudspeaker




PRODUCT OVERVIEW

IC6CLASS-TR 2-way low and high impedance loudspeaker, integrates a very careful and efficient selection of components (6" woofer + 1" tweeter), together with a mechanical design that provide a high quality audio ("Hi-Fidelity" profile sound) and a very fast installation process, just using a basic set of tools.

KEY FEATURES

- 2 way loudspeaker, 75 WRMS
- \bullet 16 Ω impedance, allowing for multiple units connected in parallel to a standard audio amplifier
- High impedance built-in transformer, allowing for multiple units connected in parallel to a 70V / 100V line audio amplifier (5 different power tappings available)
- •16 Ω or high impedance power selection accessible from the front panel, once the loudspeaker is already installed in the ceiling 6,5" Kevlar® woofer
- 1" Silk dome (ACCW) tweeter
- Aluminium front grill
- Fast installation procedure using a basic set of tools





APPLICATIONS


- Corporate and residential buildings
- Commercial premises, retail shops
- Leisure centres
- Sound reinforcement in clubs, bars, etc.
- Health and sports centres
- Meeting and conference rooms
- 5.1 and 7.1 surround systems
- Auditoriums, museums

TECHNICAL DATA


Nominal low impedance	16Ω
RMS power	75W
Power selector (70V)	1.5, 3.7, 7.5, 10, 15W
Power selector (100V)	3, 7.5, 15, 20, 30W
Frequency response (-6dB)	45Hz – 22kHz
Sensitivity 1W/1m	86dB
External diameter	270mm
Internal diameter	224mm
Recommended cut out diameter	227mm
Required depth	95mm
Weight	2,5Kg



MECHANICAL DIAGRAMS



POLAR DIAGRAMS



All product characteristics are subject to variation due to production tolerances. NEEC AUDIO BARCELONA S.L. reserves the right to make changes or improvements in the design or manufacturing that may affect these product specifications. Motors, 166-168 08038 Barcelona - Spain - (+34) 932238403 information@ecler.es **www.ecler.com**