



Product Features

40GB-Universal modular jack, shielded, for standard Keystone openings

- for use in 40-Gigabit-Ethernet Networks (bandwidth 2000 MHz)
- for use in 25-Gigabit-Ethernet Networks (bandwidth 1250 MHz)
- for use in 40-Gigabit-Ethernet Networks (bandwidth 500 MHz)
- 1 x RJ45 jack
- for standard keystone cutouts (14,8 x 19,3mm)
- zinc diecast design
- coated housing
- 360° strain relief and shielding
- suitable for cables with 6-10 mm diameter
- solid wires: IDC-terminals for one wire 0,57-0,64 mm Ø, AWG23-22, outer diameter 0,9-1,6 mm (PE)
- 1 wire for each contact, reconnectable 4-times (at the same or larger diameter)
- defined grounding via flat plug possible
- shield contact regarding to standards
- easy to mount (2 pieces)
- built-in dust protection (removable)
- colour code T568A and T568B according to TIA/EIA-568 B.2
- suitable für PoE+ (Power over Ethernet) according to IEEE 802.3at
- UPOE conform
- HDBaseT conform
- with additional mounting adapter suitable for the TAE-design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, Jung, Merten etc.)
- according to the following standards for 40Gbit:
 - ISO/IEC 11 801, Cat.8.1/Class I, shielded
 - DIN EN 50173-1, Cat.8.1/Class I, shielded
 - ANSI TIA/EIA-568-C2-1, Category 8
- according to the following standards for 25Gbit:
 - ISO/IEC TR 11801-9905
 - ISO/IEC 11801, Class I bis 1250 MHz, shielded
- according to the following standards for 10Gbit:
 - ISO/IEC 11 801, Cat.6A, shielded
 - DIN EN 50173-1, Cat.6A, shielded
 - ANSI TIA/EIA-568-C2 Category 6A
 - DIN EN 60 603-7-51, 500 MHz, shielded
- connector according to DIN EN 60603-7-1
- life > 750 cycles
- GHMT certified

Features	
General	
Surface	zinc die-cast, refined
Design	jack
shielded	Yes
Classification	Cat.8.1/Class I
PoweroverEthernet	Yes
Protection class IP	21
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921667958
Mounting types	
keystone-adapter	Yes
Dimensions/Weights without packaging	
Length mm	14,6
Width mm	34,4
Height mm	22,2
Certifications	
WEEE	Yes
GHMT	Yes
CE	Yes
RoHS conform	Yes
References	
Accessories	13900002, 13900005, 13910556, 13911501, 17000030, 17000031, 17000032, 17000033, 23900000, 23900010, 23910112, 23910118, 23911106, 23911108, 23911115, 23911116, 23911124, 39200002, 39200003, 39200012
Similar article	13900304, 13900310

