




## Desktop power supply with M12 socket on cable, additional IEC cable with SCHUKO plug

|                    |                            |
|--------------------|----------------------------|
| <b>Product-Nr.</b> | 210100-02                  |
| <b>EAN:</b>        | 4260556624914              |
| <b>Model:</b>      | Konstantspannungs-Netzteil |

|                                       |   |
|---------------------------------------|---|
| Order number:                         | 210100-02   |
| <b>Model:</b>                         | Konstantspannungs-Netzteil  |
| <b>Type:</b>                          | Desktop power supply with M12 socket on cable, additional IEC cable with SCHUKO plug              |
| <b>Cable length:</b>                  | ~1,8 m (~5,91 ft.)  |
| <b>Number of poles:</b>               | 4   |
| <b>Ambient temperature:</b>           | -30°C -> +70 °C (-22 °F -> 158 °F)  |
| <b>Nominal output voltage:</b>        | 24V DC  |
| <b>Max. output power:</b>             | 60 W  |
| <b>Output current:</b>                | 2500 mA   |
| <b>Voltage range:</b>                 | 90...264V AC  |
| <b>Input frequency:</b>               | 47...63 Hz  |
| <b>Max. input current (230 V AC):</b> | 1000 mA ± 1%  |
| <b>Max. Input current (115 V AC):</b> | 1400 mA ± 1%  |
| <b>Output voltage setting range:</b>  | 22...27V DC   |
| <b>Overvoltage protection:</b>        | 25,2 - 32,4V DC   |
| <b>Connection to a light:</b>         | M12 socket, A-coded   |
| <b>Efficiency at full load:</b>       | 90,50%  |
| <b>P no:</b>                          | <0,075 W  |
| <b>Dimensions (mm):</b>               | 125 mm x 50 mm x 31,5 mm (~4,92" x ~1,97" x ~1,24")   |
| <b>Overtemperature protection:</b>    | 75 °C ± 5 °C  |
| <b>Humidity during operation:</b>     | 20...90% (non-condensing)   |
| <b>Weight (net):</b>                  | 250 g (~9 oz)   |
| <b>Gross weight:</b>                  | 300 g (~11 oz)  |
| <b>Markings:</b>                      | EISA 2007/DoE, NRCAN, Korea K-MEPS, AU/NZ MEPS, EU, CE, UKCA                                      |
| <b>Dimmable:</b>                      | Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH        |
| <b>Protective devices:</b>            | short circuit protection, overload protection, overvoltage protection, overtemperature protection |
| <b>Feature:</b>                       | Overvoltage and overtemperature protection  |



**PIN 3 GND**  
**PIN 4 V DC**

