



Plug-in power supply with an EURO plug and a straight M12-A socket



Product-Nr.	210100-03
EAN:	4260556624921
Model:	Konstantspannungs-Netzteil
Order number:	210100-03
Model:	Konstantspannungs-Netzteil
Type:	Plug-in power supply with an EURO plug and a straight M12-A socket
Number of poles:	4
Ambient temperature:	0°C -> +40 °C (32 °F -> 104 °F)
Nominal output voltage:	24V DC
Max. output power:	36 W
Output current:	1500 mA
Voltage range:	110...240V AC
Input frequency:	50...60 Hz
Max. input current (230 V AC):	500 mA ± 1%
Max. Input current (115 V AC):	1000 mA ± 1%
Output voltage setting range:	22...27V DC
Connection to a light:	M12 socket, A-coded
Efficiency at full load:	87,40%
P no:	<0,1 W
Degree of protection:	IP20
Dimensions (mm):	73,6 mm x 42,8 mm x 32,5 mm (~2,9" x ~1,69" x ~1,28")
Humidity during operation:	20...90% (non-condensing)
Weight (net):	200 g (~7 oz)
Gross weight:	250 g (~9 oz)
Markings:	UL/cUL + TÜV EN + EN CB IEC 62368-1, FCC, CE, UKCA
Dimmable:	Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH
Protective devices:	short circuit protection, overvoltage protection, overcurrent protection
Feature:	AC interchangeable EURO plug
Note:	Not resistant to oil and cooling lubricant!

