




### Desktop power supply with M12 socket on cable, additional IEC cable with SCHUKO plug

<b>Product-Nr.</b>	210100-05
<b>EAN:</b>	4260556622064
<b>Model:</b>	Konstantspannungs-Netzteil

Order number:	210100-05
<b>Model:</b>	Konstantspannungs-Netzteil
<b>Type:</b>	Desktop power supply with M12 socket on cable, additional IEC cable with SCHUKO plug
<b>Cable length:</b>	~1,8 m (~5,91 ft.)
<b>Number of poles:</b>	4
<b>Ambient temperature:</b>	-30°C -> +70 °C (-22 °F -> 158 °F)
<b>Nominal output voltage:</b>	24V DC
<b>Max. output power:</b>	120 W
<b>Output current:</b>	5000 mA
<b>Voltage range:</b>	90...264V AC
<b>Input frequency:</b>	47...63 Hz
<b>Max. input current (230 V AC):</b>	700 mA ± 1%
<b>Max. Input current (115 V AC):</b>	1400 mA ± 1%
<b>Output voltage setting range:</b>	22...27V DC
<b>Overvoltage protection:</b>	25,2 - 32,4V DC
<b>Connection to a light:</b>	M12 socket, A-coded
<b>Efficiency at full load:</b>	89,50%
<b>P no:</b>	<0,15 W
<b>Dimensions (mm):</b>	167 mm x 67 mm x 35 mm (~6,57" x ~2,64" x ~1,38")
<b>Overtemperature protection:</b>	90 °C ± 10 °C
<b>Humidity during operation:</b>	20...90% (non-condensing)
<b>Weight (net):</b>	600 g (~21 oz)
<b>Gross weight:</b>	620 g (~22 oz)
<b>Markings:</b>	EISA 2007/DoE, NRCAN, Korea K-MEPS, AU/NZ MEPS, EU, CE, UKCA
<b>Dimmable:</b>	Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH
<b>Protective devices:</b>	short circuit protection, overload protection, overvoltage protection, overtemperature protection
<b>Feature:</b>	Overvoltage and overtemperature protection



**PIN 3 GND**  
**PIN 4 V DC**

