


## LED surface-mounted luminaire for machines



|                    |                     |
|--------------------|---------------------|
| <b>Product-Nr.</b> | 153310-01           |
| <b>EAN:</b>        | 4260556625539       |
| <b>Model:</b>      | FIELDLED EVO Aufbau |

|                            |   |
|----------------------------|---|
| Order number:              | 153310-01   |
| Model:                     | FIELDLED EVO Aufbau   |
| Type:                      | LED surface-mounted luminaire for machines  |
| Illuminant:                | SMD LED   |
| Power consumption:         | ~78 W   |
| Lamp luminous flux:        | 12000 lm  |
| Lamp luminous efficiency:  | 155 lm/W  |
| Light distribution:        | direct  |
| Light colour:              | 5600K 3-step MacAdam  |
| Connected load:            | 24V DC $\pm$ 10%  |
| Connection (connector):    | M12 A-coded, end face   |
| Degree of protection:      | IP67/IP69K  |
| Class of protection:       | III   |
| Glare control:             | Microprisms   |
| Beam angle (optics):       | 100°  |
| Operating temperature:     | -30 °C -> +60 °C (-22 °F -> 140 °F)   |
| Colour rendering (Ra):     | >85   |
| Lamps lifetime:            | > 100.000h (L80/B10)  |
| Housing material:          | aluminium   |
| Cover material:            | ESG (toughened safety glass), shatterproof  |
| Height [B] x Width [C]:    | 30 mm x 96 mm (~1,18" x ~3,78")   |
| Length [A]:                | 1040 mm (~40,94")   |
| Weight (net):              | 3450 g (~122 oz)  |
| Gross weight:              | 4250 g (~150 oz)  |
| Risk group (DIN EN 62471): | free group  |
| Markings:                  | CE, UKCA, ETL Listed (5003529)  |
| Dimmable:                  | optional via accessories  |
| Mounting accessories:      | optional; two continuous screw channels for metric screws with thread M5 on the reverse |
| Made in:                   | Germany   |

