

LED surface-mounted luminaire for machines



| | |
|--------------------|---------------------|
| Product-Nr. | 153210-01 |
| EAN: | 4260556625492 |
| Model: | FIELDLED EVO Aufbau |

| | |
|----------------------------|-----------------------------------------------------------------------------------------|
| Order number: | 153210-01 |
| Model: | FIELDLED EVO Aufbau |
| Type: | LED surface-mounted luminaire for machines |
| Illuminant: | SMD LED |
| Power consumption: | ~58 W |
| Lamp luminous flux: | 9000 lm |
| Lamp luminous efficiency: | 155 lm/W |
| Light distribution: | direct |
| Light colour: | 5600K 3-step MacAdam |
| Connected load: | 24V DC ± 10% |
| Connection (connector): | M12 A-coded, end face |
| Degree of protection: | IP67/IP69K |
| Class of protection: | III |
| Glare control: | Microprisms |
| Beam angle (optics): | 100° |
| Operating temperature: | -30 °C -> +60 °C (-22 °F -> 140 °F) |
| Colour rendering (Ra): | >85 |
| Lamps lifetime: | > 100.000h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | ESG (toughened safety glass), shatterproof |
| Height [B] x Width [C]: | 30 mm x 96 mm (~1,18" x ~3,78") |
| Length [A]: | 790 mm (~31,1") |
| Weight (net): | 2600 g (~92 oz) |
| Gross weight: | 3500 g (~123 oz) |
| Risk group (DIN EN 62471): | free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | optional via accessories |
| Mounting accessories: | optional; two continuous screw channels for metric screws with thread M5 on the reverse |
| Made in: | Germany |

