



Product Features

DIN-rail mounting adapter, with Universal modular jack UM-Cat.6A iso A, 1 DIN unit wide (1 unit 17 mm)
- for use in 10-Gigabit-Networks (transmission bandwidth 500 MHz)
- for DIN-rail mounting
- insulation class II (without earth connector)
- insulations class I (with earth connector)
- earthing connection via customary blade terminal
- RJ45-angle outlet (ra. 45°)
- plug unlocking at the frontside
- unloosable cover
- with labeling field
performance universal modular jack:
- Cat.6A iso universal module, shielded
- for use in 10-Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
- 1 x RJ45 - opening
- for standard keystone cutouts (14,8 x 19,3mm)
- zinc diecast design
- nickel-plated housing
- 360° strain relief and shielding
- suitable for Cat.6 and Cat.7 cable (Ø 6-10mm)
- solid wires: IDC-terminals for one wire 0,51 - 0,64 mm Ø, AWG 24-22, maximum number of connections > 10-times
- stranded wires: IDC-terminals for one wire Leiter 0,13-0,22 mm Ø AWG 26 (PE-Foamskin), AWG 24 (PE-solid), outer diameter 0,9-1,1 mm (PE)
- 1 wire each contact, max. number of connections > 10-times
- bend radius optimized cable entry (30°)
- defined grounding via flat plug possible
- mounting without any special tools
- built-in dust protection (removeable)
- colour code T568A and T568B according to EIA/TIA 568 A and B
- suitable for PoE++ / 4PPOE according to IEEE 802.3bt
- UPOE conform
- HDBaseT conform
- according to the following standards:
- ISO/IEC 11801, Cat.6A, shielded
- DIN EN 50173-1, Cat.6A, shielded
- ANSI TIA/EIA-568-C.2 Category 6A
- DIN IEC 60603-7-51, 500 MHz, shielded,
- life > 750 cycles
- RJ11/12-protected against mismatching

- GHMT certified

Features	
General	
Surface	high-gloss
Design	jack
Labeling field	Yes
shielded	Yes
Classification	Cat.6A iso
PoweroverEthernet	Yes
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921663813
Mounting types	
DIN-Rail	Yes
Dimensions/Weights without packaging	
Length mm	18
Width mm	73
Height mm	70
Net weight piece kg	0,052
Certifications	
WEEE	Yes
GHMT	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	1
Packaging unit Width mm	312
Packaging unit Height mm	178
Packaging unit Depth mm	87
References	
Accessories	39200002, 39200003
Similar article	13900304, 17000030

