

## Han 8 Quintax-F-c



Part number	09 15 008 3113
Specification	Han 8 Quintax-F-c
HARTING eCatalogue	<a href="https://b2b.harting.com/09150083113">https://b2b.harting.com/09150083113</a>

### Identification

Category	Inserts
Series	Han-Quintax <sup>®</sup> High Density
Description of the contact	for Han <sup>®</sup> D-Sub crimp contacts

### Version

Gender	Female
Number of contacts	8
Additional contacts	+ shielding
Details	Please order crimp contacts separately.

### Technical characteristics

Conductor cross-section	0.09 ... 0.52 mm <sup>2</sup>
Rated current	5 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Contact resistance, shielding	≤10 mΩ
Limiting temperature	-40 ... +85 °C
Mating cycles	≥500

### Material properties

Material (insert)	Polycarbonate
Colour (insert)	RAL 7032 (pebble grey)
Material (shielding)	Zinc die-cast, nickel-plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No



Pushing Performance

## Material properties

REACH ANNEX XIV substances	No
REACH SVHC substances	No

## Specifications and approvals

Specifications	EN 60664-1
	IEC 61984
UL / CSA	UL 1977 ECBT2.E102079
	CSA-C22.2 No. 182.3 ECBT8.E102079

## Commercial data

Packaging size	1
Net weight	24.42 g
Country of origin	Germany
European customs tariff number	85366990