

plug - with TE screw terminals, for harsh applications





Product description	
BALS-Prd.-Nr	2199-1
EAN	4024941410120
Product category	TE plug, TE plug
Current	125A, 125A
Number of poles	5p, 5p
Arrangement of phases	3p+N+PE, 3p+N+PE
Position of earth contact	6 h, 6 h
Voltage	200/346 - 240/415V~, 200/346 - 240/415V~
Frequency	50/60Hz, 50/60Hz

Product description	
Protection degree	IP67, IP67
Colour code	red RAL 3000, red RAL 3000
Colour of appliance	Collar red RAL 3000, Bajonet ring dark grey/black (RAL 7012/9005), Cable gland dark grey/black (RAL 7012/9005), Pusher black RAL 9005, Housing cover dark grey RAL 7012, Collar red RAL 3000, Bajonet ring dark grey/black (RAL 7012/9005), Cable gland dark grey/black (RAL 7012/9005), Pusher black RAL 9005, Housing cover dark grey RAL 7012
Connection design	screw terminal as box terminal, screw terminal as box terminal
Maximum conductor size	50.0 qmm, 50.0 qmm
Cable entry	with cable gland, with cable gland
Height	273mm, 273mm
Width	126mm, 126mm
Depth	126mm, 126mm
Material of enclosure	Polycarbonate + Polyester, Polycarbonate + Polyester
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated, The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	For cable diameter from 26 up to max. 50 mm, With rubberized cable gland (SUSTAINABLE-GRIP), Multi-Grip cable gland with gasket and integrated strain relief, With rubberized bayonet ring (SUSTAINABLE-GRIP), For cable diameter from 26 up to max. 50 mm, With rubberized cable gland (SUSTAINABLE-GRIP), Multi-Grip cable gland with gasket and integrated strain relief, With rubberized bayonet ring (SUSTAINABLE-GRIP)

Logistics data	
Weight/pcs	1307.2 g / Piece
Packaging	Bag
Content amount	1 ST
Length	126 mm
Width	126 mm
Height	273 mm
Weight	1,308.2 g
Volume	4,334.148 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941417075
Length	345 mm
Width	345 mm
Height	217 mm
Weight	6,871 g
Volume	25,828.425 ccm



Ampere Polzahl	125 3	125 4	125 5
ø a	126,0	126,0	126,0
b	171,0	171,0	171,0
d	198,0	198,0	198,0
ø e	50,0	50,0	50,0
x	268,0	268,0	268,0
y	126,0	126,0	126,0
z	126,0	126,0	126,0
Cond. mm ² min	16,0	16,0	16,0
Cond. mm ² max	50,0	50,0	50,0



